

benchlathe DKM 250L/230V

tabledrehbank with leistungsheavilyem 0,75 KW Motor, gearbox and big distance between center. ground gears in in Oil running for start fromsolut low-noise run.

Highlights

- heightre resolution the Achsspindeln for exactit Positionieren
- complete Electric in Germany by us mounted
- strengthrer Motor with 0,75 KW
- Lenze Frequentoformer

Netto: 1.950,00 €

Result (include USt.): 2.320,50 €

plus Versatdkosten

specifications

height of center	125 mm
distance between center	700 mm
Longitudinal feed	0,05 - 0,2 mm
bed width	125 mm
max. swing over bed	250 mm
max. swing over slider	130 mm
diameter of spindlehole	27 mm
speed range	115-1620 U/min in 6 steps
metric thread	0,2 - 3,5 mm (20 steps)
inch thread	8 - 56 TPI (20 steps)
model thread	0,2 - 1,25 (10 steps)
swivel range of top slider	+/-45°
longitudinal movement	700 mm
travel cross	120 mm
quill konus	morse cone 2
quill stroke	40 mm
power of engine	0,75KW/230 Volt
weight	168,00 kg
dimensions	1410 x 605 x 405 mm

equipment

- produced according DIN 8606
- 27 mm spindle bore
- adjustable guideways "by adjustable ledges"
- hardened and ground gears for low-noise run

accessoires

3-jaw chuck 120mm, change gear set, splash guard

optinalit accessory

MK2 running	27,00 €
0 mm with insert system 7- pieces	72,00 €
keyless drill chuck B18 1-16mm	25,00 €
3 - axis digital readout for lathes	269,00 €