

benchlathe DKM 250L

tabledrehbank with leistungsheavilyem 0,75 KW Motor, gearbox and big distance between center. ground gears in in Oil running for start fromsolut low-noise run. onteilung the Handwheels 0,02 mm/graduation for genauerit Positionieren the axis.

Netto: 1.845,00 €

Result (include USt.): 2.195,55 €

plus Versatdkosten

specifications

height of center	125 mm
distance between center	700 mm
bed width	125 mm
max. swing over bed	250 mm
max. swing over slider	130 mm
diameter of spindlehole	27 mm
speed range	115-1620 U/min in 6 steps
metric thread	0,2 - 3,5 mm (20 steps)
inch thread	8 - 56 TPI (20 steps)
model thread	0,2 - 1,25 (10 steps)
swivel range of top slider	+/-45°
longitudinal movement	700 mm
travel cross	120 mm
quill konus	morse cone 2
quill stroke	40 mm
power of engine	0,75KW/400 Volt
weight	152,00 kg
dimensions	1410 x 605 x 405 mm

equipment

- produced according DIN 8606
- 27 mm spindle bore
- adjustable guideways "by adjustable ledges"
- hardened and ground gears for low-noise run

accessoires

3-jaw chuck 120mm, change gear set

optinalit accessory

cooling device K45	225,00 €
2 mm with insert system 9- pieces	75,00 €
MK2 running	27,00 €
Multifix Gr. AA	298,00 €
3 - axis digital readout for lathes	269,00 €