

benchlathe DKM 280-1/500

tabledrehbank with leistungsheavilyem 0,75 KW Motor and autofeed in longitudinal and cross axis. ground gears in in Oil running for start fromsolut low-noise run. onteilung the Handwheels 0,02 mm/graduation for genauert Positionieren the axis.

Netto: 3.500,00 €

Result (include USt.): 4.165,00 €

plus Versatdkosten

specifications

height of center	140 mm
distance between center	500 mm
movement of Z-axis	500 mm
movement of X-axis	160 mm
movement Z0-Axis	75 mm
autofeed Z-axis	0.03 - 0.375 mm/U
autofeed X-axis	0.015 - 0.188 mm/U
bed width	125 mm
max. swing over bed	280 mm
max. swing over slider	165 mm
diameter of spindlehole	38 mm
speed range	90-1800 U/min in 8 steps
metric thread	0,2 - 3,5 mm (18 steps)
inch thread	4 1/2 - 48 TPI (34 steps)
model thread	0,2 - 1,75 (16 steps)
Diamentral	16 - 120DP (24 steps)
swivel range of top slider	+ -45°
longitudinal movement	700 mm
travel cross	120 mm
quill konus	morse cone 3
quill stroke	60 mm
power of engine	0,75KW/400 Volt
weight	240,00 kg
dimensions	1200 x 650 x 1200 mm

equipment

- produced according DIN 8606
- 38 mm spindle bore
- adjustable guideways "by adjustable ledges"
- hardened and ground gears for low-noise run
- 3 axis digital measurement system

accessoires

3-jaw chuck 160mm, change gear set, 3-axis digital measurement system, 1 x MK 5 dead center, 1 x MK 3 dead center, each 1 allen key 4/5/6, Wrench 12-14,17-19, german manual