

benchlathe DKM 280/500

tabledrehbank with leistungsheavilyem 0,75 KW Motor and autofeed in longitudinal and cross axis. ground gears in in Oil running for start fromsolut low-noise run. onteilung the Handwheels 0,02 mm/graduation for genauertit Positionieren the axis.

Price upon inquiry

specifications

height of center	140 mm
distance between center	500 mm
movement of Z-axis	500 mm
movement of X-axis	160 mm
movement Z0-Axis	75 mm
autofeed Z-axis	0.03 - 0.375 mm/U
autofeed X-axis	0.015 - 0.188 mm/U
bed width	125 mm
max. swing over bed	280 mm
max. swing over slider	165 mm
diameter of spindlehole	38 mm
speed range	90-1800 U/min in 8 steps
metric thread	0,2 - 3,5 mm (18 steps)
inch thread	4 1/2 - 48 TPI (34 steps)
model thread	0,2 - 1,75 (16 steps)
Diamentral	16 - 120DP (24 steps)
swivel range of top slider	+/-45°
longitudinal movement	700 mm
travel cross	120 mm
quill konus	morse cone 3
quill stroke	60 mm
power of engine	0,75KW/400 Volt
weight	240,00 kg
dimensions	1200 x 650 x 1200 mm

equipment

- produced according DIN 8606
- 38 mm spindle bore
- adjustable guideways "by adjustable ledges"
- hardened and ground gears for low-noise run

accessoires

3-B lathe chuck 160 mm with Inside-and Outside Jaws, Wrench for Chuck, Oilcan, full length splash guard, Innenvierkattschlüssel, dead center MK3, dead center MK5, Set Gstart fromelschlüssel, Set Lock screwdreher, Set hexagon socketschlüssel, german manual with Sparepart list, CE EC declaration of conformity