


# DKM 800.3 W



# DKM 800.3 W

## SPECIFICATIONS

<b>height of center</b>	400 mm
<b>distance between center</b>	3200 mm
<b>bed width</b>	1020 mm
<b>machining length</b>	3200 mm
<b>max. swing over bed</b>	800 mm
<b>guideways</b>	3
<b>max. workpiece weight</b>	6,0 to optional 8 to
<b>diameter of spindlehole</b>	50 mm
<b>speed range</b>	1 - 73 U/min; 16 steps
<b>Toolshaft Size max.</b>	80 x 25 mm
<b>Swivel range of toolholder</b>	+ - 90°
<b>travel of Top Slider</b>	400 mm
<b>quick feed cross</b>	1500 mm/min
<b>rapid feed longitudinal</b>	3600 mm/min
<b>quill diameter</b>	180 optional 200 mm
<b>quill konus</b>	metric 65;1:7
<b>power of engine</b>	22 KW
<b>weight</b>	15.125,00 kg
<b>dimensions</b>	6750 x 1612 x 1910 mm

## EQUIPMENT

- » bed width 1020 mm
- » gears diagonally dovetailed , hardend and ground
- » lubrication by integrated pump
- » adjustable main spindle bearing
- » rapid feed in longitudinal and cross
- » overload clutch in apron
- » digital readout
- » Optional with splash guard