

## Walzendrehmaschine DKM 800.4 W

Walzendrehmaschine for extreme heavy Spataratten bests suitable. The machine bitticht by your in hardenn insert erperbte Technik and very stablen bauweise.

### Price upon inquiry

#### specifications

|                            |                        |
|----------------------------|------------------------|
| height of center           | 400 mm                 |
| distance between center    | 4000 mm                |
| bed width                  | 1020 mm                |
| machining length           | 4000 mm                |
| max. swing over bed        | 800 mm                 |
| guideways                  | 3                      |
| max. workpiece weight      | 6,0 to optional 8 to   |
| diameter of spindlehole    | 50 mm                  |
| speed range                | 1 - 73 U/min; 16 steps |
| Toolshaft Size max.        | 80 x 25 mm             |
| Swivel range of toolholder | + - 90°                |
| travel of Top Slider       | 400 mm                 |
| quick feed cross           | 1500 mm/min            |
| rapid feed longitudinal    | 3600 mm/min            |
| quill diameter             | 180 optional 200 mm    |
| quill konus                | metric 65;1:7          |
| power of engine            | 22 KW                  |
| weight                     | 16.000,00 kg           |
| dimensions                 | 7550 x 1612 x 1910 mm  |

#### equipment

- bed width 1020 mm
- gears diagonally dovetailed , hardend and ground
- lubrication by integrated pump
- adjustable main spindle bearing
- rapid feed in longitudinal and cross
- overload clutch in apron
- digital readout
- Optional with splash guard

#### accessoires

Rest clamping range: 300 - 480 mm