

KAMI WERKZEUGMASCHINEN

UNIVERSAL TOOLMILLING MACHINE

FKM 950 CNC

UNIVERSAL TOOLMILLING MACHINE

FKM 950 CNC

SPECIFICATIONS

table size	800 x 400 mm
travel longitudinal (x)	500 mm
movement in Y	350 mm
movement vertical Z	400 mm
spindle speeds	0-3600 U/min
tool mounts	ISO 40 / DIN 2080
quill stroke	80 mm
rapidfeed X-Axis	6000 mm/min
rapid feed Y-axis	6000 mm/min
rapid feed Z-axis	6000 mm/min
feed range of X-axis	2 - 3000 mm/min
feed range of Y-axis	2 - 3000 mm/min
feed range of Z-axis	2 - 3000 mm/min
distance	center of spindle - table surface □35 - 435 mm
size of t-slots	7 x T14H7
power of main motor	5,5 KW
torque autofeed Z-axis	22 Nm
torque feed X-+ Y-axis	10 Nm
enginepower of cooling pump	0.1 KW
power of engine Hydraulik	0.55 KW
weight	1.300,00 kg
dimensions	1820x1640x1710 mm

EQUIPMENT

- » full cabin
- » Heidenhain TNC 7, Touchscreen 21"
- » central lubrication with Intervallschaltung
- » automatic tool mounts
- » automatic speed through S-Befehl
- » operating mode light
- » electronical Handle wheel
- » electronicalr POti

ACCESSORIES

universal toolmilling machine with Heidenhain TNC7, electronical Handle wheel, electronicalr Poti, full cabin, central lubrication with Intervallschaltung, german Operating documents