

# DKM 1000 ZS



# DKM 1000 ZS

## SPECIFICATIONS

<b>height of center</b>	500 mm
<b>distance between center</b>	6000 mm
<b>max. swing over bed</b>	1000 mm
<b>max. swing over slider</b>	630 mm
<b>bed width</b>	755 mm
<b>diameter of spindlehole</b>	130 mm
<b>spindlenose</b>	A2-15
<b>speed range</b>	3,15. - 315 U/min stepless in 4 gear steps
<b>movement of X-axis</b>	520 mm
<b>movement of Z-axis</b>	5730 mm
<b>rapid feed Z-axis</b>	7 m/min
<b>rapidfeed X-Axis</b>	6 m/min
<b>quill diameter</b>	160 mm
<b>quill stroke</b>	300 mm
<b>quill konus</b>	morse cone 6
<b>power of engine</b>	22 KW
<b>weight</b>	13.000,00 kg
<b>dimensions</b>	8800x2435x2150 mm

## EQUIPMENT

- » 4-position tool changer
- » automatic central lubrication
- » Siemens 828D
- » RS-232 interface
- » 2 Movable doors with viewing window

## ACCESSORIES

cooling device, Half cabin with 2 Movable doors,electrical Handle wheel, supervised Chuck cover,electrically propelled tailstock, controlled 4-position tool changer