

## Zyklendrehmaschine DKM 1000 ZS

Zyklendrehmaschine with 4 fach tool changer and heavilyem Servomotor and 3 gear steps. The repeat accuracy of the tool changers liegt at 0,008 mm. high rapid feed speed of X=3 m/min and Z=6 m/min.

### Price upon inquiry

#### specifications

height of center	500 mm
distance between center	6000 mm
max. swing over bed	1000 mm
max. swing over slider	630 mm
bed width	755 mm
diameter of spindlehole	130 mm
spindlenose	A2-15
speed range	3,15. - 315 U/min stepless in 4 gear steps
movement of X-axis	520 mm
movement of Z-axis	5730 mm
rapid feed Z-axis	7 m/min
rapidfeed X-Axis	6 m/min
quill diameter	160 mm
quill stroke	300 mm
quill konus	morse cone 6
power of engine	22 KW
weight	13.000,00 kg
dimensions	8800x2435x2150 mm

#### equipment

- 4-position tool changer
- automatic central lubrication
- Siemens 828D
- RS-232 interface
- 2 Movable doors with viewing window

#### accessoires

cooling device, Half cabin with 2 Movable doors, electrical Handle wheel, supervised Chuck cover, electrically propelled tailstock, controlled 4-position tool changer