

KAMI WERKZEUGMASCHINEN

ZYKLENDREHMASCHINE

# DKM 550 FTL/1000

# DKM 550 FTL/1000

## SPECIFICATIONS

<b>height of center</b>	275 mm
<b>distance between center</b>	1000 mm
<b>bed width</b>	500 mm
<b>max. swing over bed</b>	550 mm
<b>max. swing over slider</b>	350 mm
<b>speed</b>	0 - 1000 U/min
<b>diameter of spindlehole</b>	120 mm
<b>max. Diameter through Spindle</b>	110 mm
<b>spindlenose</b>	A2-11
<b>movement of X-axis</b>	280 mm
<b>movement of Z-axis</b>	1000 mm
<b>quill stroke</b>	100 mm
<b>quill konus</b>	morse cone 5
<b>power of engine</b>	15 KW
<b>weight</b>	4.500,00 kg
<b>dimensions</b>	3500x1600x2010 mm

## EQUIPMENT

» 8-fach tool changer, SIEMENS 828D SW24x, tailstock, elektron. Handwheels for Z+X-axis, working lamp, cooling device, automatic central lubrication, Toolbox, german Operating documents, CE conformity

## ACCESSORIES

3-B lathe chuck 380 mm, cooling device, 8 Station tool changer, automatic central lubrication, Siemens 828D SW24x, RS 232 interface, 2 Movable doors with viewing window