

# DKM 630/1000 LT



# DKM 630/1000 LT

## SPECIFICATIONS

<b>height of center</b>	325 mm
<b>distance between center</b>	1000 mm
<b>max. swing over bed</b>	650 mm
<b>max. swing over slider</b>	375 mm
<b>diameter of spindlehole</b>	105 mm
<b>spindlenose</b>	A1-11
<b>speed range</b>	10 - 850 U/min 3 gear steps
<b>movement of X-axis</b>	370 mm
<b>movement of Z-axis</b>	760 mm
<b>rapid feed Z-axis</b>	5 m/min
<b>rapidfeed X-Axis</b>	4 m/min
<b>quill diameter</b>	100 mm
<b>quill stroke</b>	250 mm
<b>quill konus</b>	morse cone 5
<b>power of engine</b>	11 KW
<b>weight</b>	4.000,00 kg
<b>dimensions</b>	3300x1900x1900 mm

## EQUIPMENT

- » 12-fold tool changer for live tools
- » automatic central lubrication
- » Fanuc Oi-MATE or Siemens 828D control system
- » RS-232 interface
- » 2 Movable doors with viewing window

## ACCESSORIES

FANUC MATE Oi or SIEMENS 828D control system, electrical Handle wheel, 12-fold tool changer for live tools, central lubrication, cooling device, . german Operating documents