

## Zyklendrehmaschine DKM 800.2 ZS

Zyklendrehmaschine with 4 fach tool changer and heavilyem Servomotor and 3 gear steps. The repeat accuracy of the tool changers liegt at 0,008 mm. high rapid feed speed of X=6 m/min and Z=7 m/min.

### Price upon inquiry

#### specifications

|                         |                              |
|-------------------------|------------------------------|
| heigth of center        | 400 mm                       |
| distance between center | 2000 mm                      |
| max. swing over bed     | 800 mm                       |
| max. swing over slider  | 500 mm                       |
| bed width               | 560 mm                       |
| diameter of spindlehole | 105 mm                       |
| spindlenose             | A1-11                        |
| speed range             | 20 - 1120 U/min 3 gear steps |
| movement of X-axis      | 390 mm                       |
| movement of Z-axis      | 1760 mm                      |
| rapid feed Z-axis       | 7 m/min                      |
| rapidfeed X-Axis        | 6 m/min                      |
| quill diameter          | 100 mm                       |
| quill stroke            | 250 mm                       |
| quill konus             | morse cone 5                 |
| power of engine         | 11 KW                        |
| weight                  | 5.800,00 kg                  |
| dimensions              | 4500x1680x2000 mm            |

#### equipment

- 4-position tool changer
- automatic central lubrication
- Fanuc Oi-MATE control system
- RS-232 interface
- 2 Movable doors with viewing window

#### accessoories

cooling device