

KAMI WERKZEUGMASCHINEN

ZYKLENDREHMASCHINE

# DKM 800x2000 ZS



# DKM 800x2000 ZS

## SPECIFICATIONS

|                                |                              |
|--------------------------------|------------------------------|
| <b>height of center</b>        | 400 mm                       |
| <b>distance between center</b> | 2000 mm                      |
| <b>max. swing over bed</b>     | 800 mm                       |
| <b>max. swing over slider</b>  | 500 mm                       |
| <b>bed width</b>               | 560 mm                       |
| <b>diameter of spindlehole</b> | 105 mm                       |
| <b>spindlenose</b>             | A1-11                        |
| <b>speed range</b>             | 20 - 1120 U/min 3 gear steps |
| <b>movement of X-axis</b>      | 390 mm                       |
| <b>movement of Z-axis</b>      | 760 mm                       |
| <b>rapid feed Z-axis</b>       | 7 m/min                      |
| <b>rapidfeed X-Axis</b>        | 6 m/min                      |
| <b>quill diameter</b>          | 100 mm                       |
| <b>quill stroke</b>            | 250 mm                       |
| <b>quill konus</b>             | morse cone 5                 |
| <b>power of engine</b>         | 11KW optional 15KW           |
| <b>weight</b>                  | 5.650,00 kg                  |
| <b>dimensions</b>              | 4600x1680x2000 mm            |

## EQUIPMENT

- » 4-position tool changer nor. 6-position Toolchanger
- » automatic central lubrication
- » Fanuc Oi-MATE or. SIEMENS 828D control system
- » RS-232 interface
- » elektrontheyit Handle wheel
- » 2 Movable doors with viewing window

## ACCESSORIES

cooling device, full cabin, electronical Handle wheel, LED-operating mode light, deutschsprachige Operating documents, CE EC declaration of conformity, Siemens 828D or. FANUC OI MATE