

Zyklendrehmaschine DKM 800x2000 ZS

Zyklendrehmaschine with 4 fach or. 6-position tool changer and heavyem Servomotor and 3 gear steps. The repeat accuracy of the tool changers liegt at 0,008 mm. high rapid feed speed of X=6 m/min and Z=7 m/min.

Price upon inquiry

specifications

height of center	400 mm
distance between center	2000 mm
max. swing over bed	800 mm
max. swing over slider	500 mm
bed width	560 mm
diameter of spindlehole	105 mm
spindlenose	A1-11
speed range	20 - 1120 U/min 3 gear steps
movement of X-axis	390 mm
movement of Z-axis	760 mm
rapid feed Z-axis	7 m/min
rapidfeed X-Axis	6 m/min
quill diameter	100 mm
quill stroke	250 mm
quill konus	morse cone 5
power of engine	11KW optional 15KW
weight	5.650,00 kg
dimensions	4600x1680x2000 mm

equipment

- 4-position tool changer nor. 6-position Toolchanger
- automatic central lubrication
- Fanuc Oi-MATE or. SIEMENS 828D control system
- RS-232 interface
- elektrontheyit Handle wheel
- 2 Movable doors with viewing window

accessoires

cooling device, full cabin, electronical Handle wheel, LED-operating mode light, deutschsprachige Operating documents, CE EC declaration of conformity, Siemens 828D or. FANUC OI MATE